

User Manual

# Plenum DVI Dual Link Male/Male Cable ATP-14009







## DESCRIPTION

Rated Voltage (V)	-
Rated Temperature (°C)	75
Product Standard Certification	CL2P
Flame test	NFPA 262/UL910


#### Application

Power-limitecl circuit cables for use a fixed wiring within buildings (some are also marked for direct burial) principally for class 3 and class 2 circuits.

#### **Reference Standard**

UL 13

## **CROSS SECTION**



### COLOR

#### Insulation:

Component A:	P1 .White8	k Red	P2.White&Green	
	P3.White&	Blue	P4.White& Brown	
	P5:White&	Orange	P6:White&Yellow	P7:White&Purple
Component B:	Yellow & Orange			
Component C:	1.Black	2.Brown	3.Red	

#### Jacket Matte Black(KJBH)



## CONSTRUCTION

Conductor	Stranded Tinned Copper			
Component A:	(1 Pair +Drain Wire+ Shield)x7 14C			
AWG	24			
Construction (mm)	7/0.20T			
Stranded Dia.(mm)	0.60			
Insulation	FOAM FEP			
Nom. Thickness (mm)	0.42			
Insulation Dia.( ±0.05mm)	1.45			
Drain Wire	7/0.20T			
Shield	E-F-E Aluminum/Polyester			
Coverage(%)	>=125%			
Component B :1P	1P			
Conductor	Stranded Tinned Copper			
AWG	24			
Construction (mm)	7/0.20T			
Stranded Dia.(mm)	0.60			
Insulation	FEP			
Nom. Thickness (mm)	0.17			
Insulation Dia.( ±0.05mm)	0.95			
Component C : 3C	3C			
Conductor	Stranded Tinned Copper			
AWG	24			
Construction (mm)	7/0.20T			
Stranded Dia.(mm)	0.60			
Insulation	FEP			
Nom. Thickness (mm)	0.17			
Insulation Dia.( ±0.05mm)	0.95			
Component A+B+C Cabling Together Shield				
Shield	Aluminum/Polyester			
Coverage(%)	>=125%			
Drain Wire(Stranded Tinned Copper)	7/0.20T			
Braid Shield	Tinned Copper			
Construction(mm)	24/9/0.12T			
Coverage(%)	>=85%			
Jacket	Plenum-PVC			
Nom. Thickness(mm)	0.55			
Outer Dia.(± 0.20mm)	10.5			



### PERFORMANCE

#### Electrical Characteristics(20°C)

Max. Conductor DC Resistance ( $\Omega$ /km) Min. Insulation DC Resistance ( $\Omega$ /km)

Dielectric Strength

#24:93 FOAM FEP:100M FEP:100M AC-500V/1 Min

#### **Mechanical Characteristics:**

Test Object Test Material Before Tensile Strength (kg/mm2) Jacket Plenum- PVC >=1.05



## SAFETY INFORMATION

Safeguards



To reduce the risk of electric shock, do not expose this product to rain or moisture



If the wall plug does not fit into your local power socket, hire an electrician to replace your obsolete socket.

	[	I	]
	[	I	]

K

Do not modify the wall plug. Doing so will void the warranty and safety features.

This equipment should be installed near the socket outlet and the device should be easily accessible in the case it requires disconnection.

Precautions

FCC regulations state that any unauthorized changes or modifications to this equipment, not expressly approved by the manufacturer, could void the user's authority to operate this equipment.

Operate this product using only the included external power supply. Use of other power supplies could impair performance, damage the product, or cause fires.

In the event of an electrostatic discharge this device may automatically turn off. If this occurs, unplug the device and plug it back in.

Protect and route power cords so they will not be stepped on or pinched by anything placed on or against them. Be especially careful of plug-ins or cord exit points from this product.

Avoid excessive humidity, sudden temperature changes or temperature extremes.

Keep this product away from wet locations such as bathtubs, sinks, laundries, wet basements, fish tanks, and swimming pools.

Use only accessories recommended by Atlona to avoid fire, shock, or other hazards.

Unplug the product before cleaning. Use a damp cloth for cleaning and not cleaning fluid or aerosols. Such products could enter the unit and cause damage, fire, or electric shock. Some substances may also mar the finish of the product.

Never open, remove unit panels, or make any adjustments not described in this manual. Attempting to do so could expose you to dangerous electrical shock or other hazards. It may also cause damage to your ATP-14009. Opening the product will void the warranty.

Do not attempt to service the unit. Disconnect the product and contact your authorized Atlona reseller or contact Atlona directly.



## WARRANTY

#### Limited Warranty

Atlona Technologies warrants that (a) its products (the ATP-14009) will perform substantially in accordance with the accompanying written materials for a period of 3 years from the date of receipt and (b) that the product will be free from defects in materials and workmanship under normal use and service for a period of 3 years. In the event applicable law imposes any implied warranties, the implied warranty period is limited to 3 years from the date of receipt. Some jurisdictions do not allow such limitations on duration of an implied warranty, so the above limitation may not apply to customers that fall within those areas.

#### **Customer Remedies**

Atlona Technologies' and its suppliers' entire liability and Customer's exclusive remedy shall be, at Atlona Technologies' decision, either return of the price paid for the product, repair, or replacement of the product that does not meet this Limited Warranty and which is returned to Atlona Technologies with a copy of the Customer's receipt. This Limited Warranty is void if failure of the product has resulted from accident, abuse, misapplication, or natural occurrence. In example but not limited to: power surges (electrical storms, local power outage), dropping the product (or items on the product), contact with fluids, and physical misconduct (i.e. kicking or punching). Any replacement product will be warranted for the remainder of the original warranty period.

#### No other warranties

To the maximum extent permitted by applicable law, Atlona Technologies and its suppliers disclaim all other warranties, either expressed or implied, including, but not limited to, implied warranties of merchantability and fitness for a particular purpose, with regard to the product and any related written materials. This Limited Warranty gives customer specific legal rights. Customers may have other rights depending on the jurisdiction.

#### No liability for damages

To the maximum extent permitted by applicable law, in no event shall Atlona Technologies or its suppliers be liable for any damages arising out of the use of or inability to use this product, even if Atlona Technologies has been advised of the possibility of such damages. Such damages include but are not limited to: special, incidental, consequential, or indirect damages for personal injury, loss of business profits, business interruption, loss of business information, or any other pecuniary loss. Atlona Technologies' and its suppliers' entire liability under any provision of this agreement shall be limited to the amount actually paid by you for the product. Some Jurisdictions do not allow the exclusion or limitation of liability for consequential or incidental damage. The above limitations may not apply to you in such jurisdictional cases.



## ATLONA PRODUCT REGISTRATION

Thank you for purchasing this Atlona product. - We hope you enjoy it and will take an extra few moments to register your new purchase.

Registration creates an ownership record if your product is lost or stolen and helps ensure you'll receive notification of performance issues and firmware updates.

At Atlona, we respect and protect your privacy, assuring you that your registration information is completely secure. Atlona product registration is completely voluntary and failure to register will not diminish your limited warranty rights.

To register go to: http://www.atlona.com/registration